SODIMM DDR3 PC3-8500 1066MHz

Features

- Fully PC3-8500 Compliant
- JEDEC-Standard 204-pin Small Outline Dual Inline Memory Module (SODIMM)
- Unbuffered
- Cas Latency 7
- Power Supply: 1.5 V ± 0.2 V
- Pure Power and Ground Planes
- Gold PCB connector

Ordering Information

	DENSITY	REFERENCE	EAN
Optima	2GB	SODI102GBN/8500/3-BX	3536401462378
Optima	Kit 4GB (2x2GB)	K-SODI4GBN/8500/3-BX	3536401002628
Premium	2GB	S2GBN16Q1066E-SB	3536401462392
Premium	Kit 4GB (2x2GB)	KS4GBN16Q1066E-SB	3536401002635

Some of our capacities are also available in Premium packagings for distribution and integration purposes.

Optima packaging

Premium packaging

Not sure of your memory needs ?

Try our online configurator !

PNY.EU

Product and specifications discussed here in are for evaluation and reference purpose only and are subject to change by PNY Technologies without notice.

For more information, visit : WWW.PNY.EU

PNY Technologies Europe - RCS Bordeaux B394790430. PNY, PNY Technologies and the PNY logo are registered trademarks of PNY Technologies Inc. All other trademarks and logos are the property of their respective companies. Copyright©2009 PNY Technologies, Inc. All rights reserved.